



# Campi di applicazione




Peso max dell'anta 110 Kg

2700	•	•	•	•	42	37	37	29	25	22	21	19	16	15	13	12	11	10	10	9
2600	•	•	•	•	44	39	38	31	26	22	22	19	17	15	14	13	12	11	10	9
2500	•	•	•	•	46	40	40	32	27	23	23	20	18	16	15	13	12	11	11	10
2400	•	•	•	•	48	42	42	34	28	25	25	21	19	17	15	14	13	12	11	10
2300	•	•	•	•	44	44	35	29	26	26	22	20	18	16	15	13	12	12	11	
2200	•	•	•	•	47	46	37	31	27	27	23	21	19	17	15	14	13	12	11	
2100	•	•	•	•	49	49	39	33	29	29	25	22	20	18	16	15	14	12	11	
2000	•	•	•	•	41	35	30	30	26	23	21	19	17	16	14	12	11			
1900	•	•	•	•	44	37	32	32	28	25	22	20	18	16	14	12	11			
1800	•	•	•	•	47	39	34	34	29	26	23	21	19	16	14	12	11			
1700	•	•	•	•	50	41	36	36	31	28	25	23	19	16	14	12	11			
1600	•	•	•	•	44	39	39	34	30	27	23	19	16	14	12	11				
1500	•	•	•	•	48	42	42	36	32	28	23	20	16	14	12	10				
1400	•	•	•	•	45	45	39	35	28	23	20	16	14	12	10					
1300	•	•	•	•	49	49	42	35	29	23	20	16	14	12	9					
1200	•	•	•	•	45	35	29	24	20	16	13	10	7							
1100	•	•	•	•	45	36	29	24	20	15	11	7	5							
1000	•	•	•	•	45	36	29	24	17	12	8	5	X	X	X	X				
900	•	•	•	•	46	36	28	19	13	8	4	X	X	X	X					
800	•	•	•	•	46	34	22	13	7	X	X	X	X	X						
700	•	•	•	•	41	25	14	6	X	X	X	X	X	X						
	360	460	509	510	610	710	794	795	900	1000	1100	1200	1300	1400	1500	1600	1700			



Peso max dell'anta 140 Kg

2700	•	•	•	•	48	48	39	32	28	28	24	22	19	18	16	15	14	13	12	
2600	•	•	•	•	40	34	29	29	25	23	20	18	17	15	14	13	12			
2500	•	•	•	•	42	35	31	31	27	24	21	19	17	16	15	14	13			
2400	•	•	•	•	44	37	32	32	28	25	22	20	18	17	16	15	14			
2300	•	•	•	•	46	38	34	34	29	26	23	21	19	18	16	15	14			
2200	•	•	•	•	48	40	35	35	31	27	24	22	20	19	17	16	15			
2100	•	•	•	•	42	37	37	32	29	26	23	21	20	18	17	16				
2000	•	•	•	•	45	39	39	34	30	27	25	22	21	19	18	17				
1900	•	•	•	•	47	42	42	36	32	29	26	24	22	20	19	17				
1800	•	•	•	•	44	44	38	34	30	28	25	23	21	19	17					
1700	•	•	•	•	47	47	41	36	32	29	27	25	22	19	17					
1600	•	•	•	•	44	39	35	31	29	26	22	19	17							
1500	•	•	•	•	47	42	37	34	31	26	22	19	17							
1400	•	•	•	•	45	40	36	31	26	22	19	17								
1300	•	•	•	•	49	44	37	31	26	22	19	17								
1200	•	•	•	•	45	37	31	26	22	19	17									
1100	•	•	•	•	45	37	31	26	22	18	14									
1000	•	•	•	•	45	37	31	26	20	16	12									
900	•	•	•	•	45	37	30	23	17	12	9									
800	•	•	•	•	46	34	25	18	12	8	5									
700	•	•	•	•	39	27	18	11	6	X	X									
	360	460	509	510	610	710	794	795	900	1000	1100	1200	1300	1400	1500	1600	1700			





Eseguibile con spessore max del vetro di 50 mm

Eseguibile con spessore max del vetro indicato (es. 20 mm)

Non eseguibile

Peso max dell'anta 170 Kg

2700	•	•	•	•	48	40	35	35	30	27	24	22	20	18	17	16	15			
2600	•	•	•	•	50	41	36	36	31	28	25	23	21	19	18	16	15			
2500	•	•	•	•	43	38	38	33	29	26	24	22	20	18	17	16				
2400	•	•	•	•	45	40	40	34	30	27	25	23	21	19	18	17				
2300	•	•	•	•	47	42	41	36	32	29	26	24	22	20	19	17				
2200	•	•	•	•	50	44	44	38	33	30	27	25	23	21	19	17				
2100	•	•	•	•	46	46	40	35	32	29	26	24	22	19	17					
2000	•	•	•	•	48	48	42	37	33	30	28	25	22	19	17					
1900	•	•	•	•	44	39	35	32	29	26	22	19	17							
1800	•	•	•	•	47	42	37	34	30	26	22	19	17							
1700	•	•	•	•	44	40	36	30	26	22	19	17								
1600	•	•	•	•	48	43	36	30	26	22	19	17								
1500	•	•	•	•	44	36	31	26	22	19	17									
1400	•	•	•	•	44	36	31	26	22	19	17									
1300	•	•	•	•	44	37	31	26	22	19	17									
1200	•	•	•	•	45	37	31	26	22	19	17									
1100	•	•	•	•	45	37	31	26	22	18	14									
1000	•	•	•	•	45	37	31	26	20	16	12									
900	•	•	•	•	45	37	30	23	17	12	9									
800	•	•	•	•	46	34	25	18	12	8	5									
700	•	•	•	•	39	27	18	11	6	X	X									
	360	460	509	510	610	710	794	795	900	1000	1100	1200	1300	1400	1500	1600	1700			



Eseguibile con spessore max del vetro di 50 mm

Eseguibile con spessore max del vetro indicato (es. 20 mm)

Non eseguibile